



RIDOUT & MAYBEE

Patent & Trade-Mark Agents



P. Ewan McArdle
B.Sc. (Mech. Eng.)

W. Charles Kent
B.Sc. (Eng. Chem.), LL.B., P.Eng.

William R. Edgar
B.Sc. (Chem. Eng.), LL.B.

Richard A.R. Parsons
B.A. (Hons.) Oxon

Philip K. Holland
M.A. Cantab.

James R. Lake
Ph.D., (Pharm. Chem.), LL.B.

Janet M. Fuhrer
LL.B.

William B. Vass
B.A.Sc. (Elec. Eng.), LL.B., P.Eng.

Robert G. Hiron
B.Sc. (Hons. Chem.)

Danall S. Mitchell
Ph.D. (Polymer. Chem.), LL.B.

Kam A. Brulé
B.A.

Marcus T. Gallie
B.Sc., M.Sc., LL.B.

Mary L. Malvaso

Lynda E.E. Doxsee

Roland H. Joachim
B.Sc. (Chem.), LL.B.

Mitchell B. Charness
B.A. Sc. (Mech. Eng.), LL.B.

Ian G. McMillan
B.Sc.E. (Mech./Math.), LL.B.

David J. Heller
B.Sc. (Biol./Chem.), LL.B.

Consultants

William L. Hayhurst

Godfrey P. Orleans

Kenneth M. Garrett

Our Ref: 33632-0312

October 15, 1999

THE COMMISSIONER OF PATENTS AND TRADEMARKS WASHINGTON, D.C. 20231

Dear Sir:

We enclose the documents identified below in respect of a patent application in the name of Quinton Lyon for an invention entitled: **ACOUSTIC PULSE-ECHO RANGING SYSTEMS** to be filed on receipt.

Enclosed are: Specification, Claims & Abstract
Declaration, Power of Attorney - unsigned
Two Sheets of Drawings (6 Figures)

This application claims Convention priority from U.K. Patent Application No. 9823059.2 filed on October 21, 1998.

	CLAIMS FILED		BASIC FEE
	Number Rate	Excess	\$
Total claims	7 -20 =	x	
Independent claims	1 - 3 =	x	
Multiple dependencies			
	Total filing fees		\$

.../2

One Queen St. East
Suite 2400, Toronto
Canada, M5C 3B1

Telephone 416.868.1482
Facsimile 416.362.0823
Email ridbee@ridoutmaybee.com

Also at 150 Metcalfe St.
18th Floor, Ottawa
Canada, K2P 1P1

RIDOUT & MAYBEE


Page 2

October 15, 1999

The Commissioner of Patents and Trademarks

Should any Patent and Trademark Office Official want to telephone, the call should be made to Richard A.R. Parsons (Registration No. 28,159) at (416) 868-1482.

Yours very truly,

A handwritten signature in dark ink, appearing to read 'R.A.R. Parsons', written over a horizontal line.

Richard A.R. Parsons
(Registration No. 28,159)

RARP/pl

Encls.

668101-226TH0

ACOUSTIC PULSE ECHO RANGING SYSTEM

FIELD OF THE INVENTION

This invention relates to pulse echo ranging systems, and more particularly although not exclusively to systems for
5 monitoring the level of sludge in a body of liquid.

BACKGROUND OF THE INVENTION

In a number of applications, it is necessary to monitor liquids containing significant quantities of suspended materials, which materials may tend to separate or
10 accumulate as a separate phase beneath a body of clearer liquid. A parameter which it is frequently desired to monitor is the level of the interface between settled material or sludge, and a supernatant liquid.

Suspended material in liquids tends to reflect or disperse
15 acoustic energy, although the extent of this effect is frequency dependent. The effectiveness of a pulse echo ranging system in determining the position of an interface between a sludge layer and a supernatant liquid will depend upon the presence of suspended material, including gas
20 bubbles, in the supernatant layer, and the concentration and nature of particles in the sludge layer. It is difficult to select a transducer frequency which will provide reliable detection of the interface under all circumstances.

25 Since transducers used in such systems will normally operate submerged, there is the possibility of build-up of material passing out of suspension and liquid and building up on the transducer assembly. Such build-up can be inhibited by ultrasonic insonification of vulnerable
30 surfaces, particularly the radiating surface of the transducer assembly, but in practice, the most effective

frequencies for operation of the transducer, if it is to be self-cleaning, often fall in a different range from those providing best detection of the sludge/liquid interface.

UK Patent Application 2054851A discloses a sonar system using multiple frequencies, one of which is generated by the beating of two closely spaced higher frequencies. UK Patent Application 2191055A discloses a radar system operating at two substantially different frequencies in order to detect flocks of birds.

10 SUMMARY OF THE INVENTION

According to the invention, a method of operating a pulse echo ranging system comprises operating a transducer assembly to provide transmission and reception of pulses of high frequency energy at plural substantially different frequencies, and signals received by the transducer assembly are to generate an echo profile for signals received at at least a first of the frequencies, and utilizing the signal at another of the frequencies to enhance the recovery of data beyond that obtained from the first signal alone.

This enhancement may be achieved in various ways. Of two frequencies, one may be used to generate an echo profile and the other to clean the radiating surface of the transducer to maintain efficiency. If echo profiles are recovered for two or more frequencies, the additional profiles may be utilized to enhance the reliability of recovery wanted data. For example, if supernatant liquid contains large quantities of suspended material, acoustic energy at a frequency best suited to detecting a sludge interface may be so attenuated before reaching the interface that detection is not practicable. In this case, the lower frequency signal may provide additional penetration in order to detect the sludge interface and

thus improve reliability.

Furthermore, if two or more echo profiles are recovered, the profile recovered from a signal which is not heavily reflected by a sludge interface or other interface which it is desired to detect may be utilized as a reference signal against which echoes occurring in the echo profile from a signal at a different frequency may be assessed. Alternatively, the profiles from different frequencies may be summed, or differenced on the basis that the response from an interface to be detected to signals at substantially different frequencies will be substantially different.

If the echo responses at different frequencies are available, it may be possible to deduce characteristics such as quantities of suspended solids, layer density, presence of bubbles, and so on from the different responses to the different frequencies.

These various features may of course be used in combination, according to the manner in which a microcontroller controlling the system is programmed.

Further features of the invention will become apparent from the following description with reference to the accompanying drawings.

SHORT DESCRIPTION OF THE DRAWINGS

Figure 1 is a simplified schematic diagram of a pulse echo ranging system;

Figure 2 is a section through a settling tank illustrating an exemplary operational environment for the mechanism;

Figure 3 is a graph illustrating an exemplary echo profile produced by a signal component at one of the frequencies utilized;

Figure 4 compares echo responses at two different
5 frequencies in a primary clarifier;

Figure 5 compares echo response at the two different frequencies in a secondary clarifier;

Figure 6 is an annotated graph illustrating how echo
10 data may be interpreted to provide additional data.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to Figure 1, there is shown a simplified schematic diagram of a pulse echo ranging system controlled by a central processing unit (CPU) 2. Typically the CPU 2
15 will be incorporated in a microcontroller implementing peripheral functions used to implement some of the other blocks shown in Figure 1 as well as additional functions not described. The CPU operates under a control program stored in read-only memory (ROM) 4, utilizing parameters
20 stored in non-volatile random access memory (NOVRAM) 6, and provided with working memory in the form of random access memory (RAM) 8. An interface 10 provides for the export of data from the unit, and the import of operating parameters. Data may be exported in the form of a display, telemetry
25 signals or alarm signals. The CPU 2 also controls a transmitter 12 which controls the timing, frequency and amplitude of high frequency pulses applied to a transducer 14. A receiver 16 receives return echo signals from the same or a different transducer, amplifies them, usually
30 logarithmically, and applies them to an analog to digital converter 18, from where the digital echo profile is stored in RAM 8 for further processing

The operation of such systems is described in more detail in our U.S. Patents Nos. 4,596,144; 4,831,565; 4,890,266; 4,999,998 and 5,076,751, and only features of difference will be discussed further below.

5 Referring to Figure 2, this shows an exemplary application of the invention, used for monitoring a sludge interface 20 in a tank 22, of the invention, in which the transducer 14 is mounted with at least its radiating face 24 submerged in the liquid content of the tank. Above the interface 20,
10 the liquid content is liquid containing suspended material and possibly gas bubbles, while a denser sludge phase 28 settles out beneath the interface and above the bottom wall 30 of the tank.

Figure 3 illustrates an exemplary echo response to a high
15 frequency acoustic pulse emitted by the transducer 14. In this instance there is a strong echo 32 from the bottom of the tank, while the weaker true echo 34 from the interface 20 shows little increase in amplitude relative to the immediately preceding portion of the profile which consists
20 not only of a component due to ranging of the transducer, but also energy reflected by the suspended material in the liquid above the interface. This reflected energy tends to mask the wanted echo.

These phenomena are illustrated further in Figures 4 and 5,
25 which show how the responses to different pulse frequencies can change in different environments. Graphs a and b in each Figure represent logarithmic plots of the amplitude of the echo profiles produced at 44 kHz and 150 kHz respectively in a tank acting as a primary clarifier and a
30 tank acting as a secondary clarifier. In Figure 4, the lower frequency (trace b) propagates well through liquid containing substantial amounts of suspended material, and

clear echoes 32 and 34 can be seen both from the bottom of the tank and the sludge interface. At the higher frequency (trace a), absorption and scattering result in the echo 34 being much less marked, and

5 the echo 32 being wholly absent. By contrast, behaviour in the secondary clarifier is quite different. In this case the suspended material is light and "fluffy". It is penetrated well by the higher frequency (trace a), providing clear echoes 32 and 34 from the bottom of the
10 tank and the sludge interface, whereas the lower frequency is severely attenuated and produces no recognizable echoes.

In a presently preferred embodiment, both frequencies are generated simultaneously by a common acoustic transducer. Piezoelectric transducers used in acoustic ranging systems
15 are commonly capable of resonating in different modes having substantially different resonant frequencies, and the transmitter 12 is configured to generate energy at two such widely spaced frequencies such as to cause the transducer to radiate at both frequencies during a pulse.
20 For best results, the frequencies should have at least 2:1 ratio. Exemplary frequencies are 44 kHz and 150 kHz, or 50 kHz and 120 kHz. It is possible to use more than two frequencies, or to use a transducer assembly containing multiple piezoelectric elements having different
25 frequencies, or to energize the transducer at different frequencies sequentially. It is also possible to utilize a transducer assembly comprising two separate transducers, for example two acoustic transducers operating at different frequencies. In some applications, it may be possible to
30 combine an acoustic microwave transducer so as to exploit the different penetration and dispersion characteristics of the different types of radiation involved, for example, in applications where it is desired to detect both a foam interface and a liquid interface in a tank with the
35 transducer assembly above both levels.

Regardless of the transmitter and transducer system used, there are various ways of using the invention to provide enhanced performance. At a lowest level, a higher frequency is used to generate an echo response for
5 analysis, and acoustic energy at a lower frequency is used to inhibit deposition of solids on a radiating surface of the transducer assembly thus improving reliability. Preferably however, echo responses are obtained at each frequency and combined in some manner to provide enhanced
10 data.

For example, the echo responses may simply be summed, providing a combined response in which echoes of energy occurring at any of the frequencies will normally be apparent. Even though one frequency fails to provide a
15 substantial echo response from a feature of interest, the second frequency may result in a satisfactory response. An alternative or additional approach is to difference the responses at two frequencies. The resulting combined response will then represent the differences between the
20 reflective behaviour of targets at the two frequencies and may enable distinct echo responses to be detected where the summary approach fails. A frequency which does not provide good echo responses may nonetheless be used as a reference against which to detect peaks or discontinuities in
25 response at another frequency.

Comparing responses at different frequencies may permit further characteristics of liquid in a vessel to be determined, since the response to different types of suspended material at different frequencies is different.
30 Referring to Figure 6, a portion of the echo profile 36 consists of reverberation from suspended particles in the supernatant liquid, a portion 38 preceding the peak 34 from the sludge interface represents enhanced reflection from

“fluff” of particle gathering above the interface, while the sharply depressed portion 40 of the response between the peak 34 and the peak 32 representing the reflection from the bottom of the tank represents high absorptive properties of the sludge beneath the interface. It will also be noted that the actual peak 34 due to reflection at the interface is quite small, but the peak is emphasized by the sharply contrasting reflective properties of the layers on either side of the peak. At a higher frequency, the reverberation from the suspended particles will typically be greater, and while the reflection from the interface may produce a more marked peak, this may be masked to a greater extent by reverberation. On the other hand, the reflection and dispersion by the fluff may be substantially less. These differing responses may permit substantial interpretation of systems whose characteristics have been the subject of empirical observation.

CLAIMS

1. A method of operating a pulse echo ranging system comprising a transducer assembly to provide transmission and reception of pulses of high frequency energy at plural substantially different frequencies, using signals received by the transducer assembly to generate an echo profile for signals received at at least a first of the frequencies, and utilizing the signal at another of the frequencies to enhance the recovery of data beyond that obtained from the first signal alone.
2. A method according to claim 1, wherein the high frequency energy is acoustic energy and one frequency is used to generate an echo profile, and a second frequency to insonify a radiating surface of the transducer assembly to render it self cleaning.
3. A method according to claim 1, wherein the received signals are used to generate an echo profile for signals received at two frequencies, and the profile combines data from the at least two signals.
4. A method according to claim 3, wherein the received signals are summed.
5. A method according to claim 3, wherein the received signals are differenced.
6. A method according to claim 3, wherein a signal received at a second frequency is used as a reference against which the first signal can be compared to detect echoes in the latter.
7. A pulse-echo ranging system including a control computer programmed to perform the method of claim 3.

ABSTRACT

A method of operating a pulse echo ranging system comprising a transducer assembly for providing transmission and reception of high frequency energy pulses at substantially different plural frequencies. The method uses signals received by the transducer assembly to generate an echo profile for signals received at at least a first of the frequencies to enhance the recovery of data beyond that obtained from the first signal alone.

094903 10189
668707 22667460




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

DECLARATION, POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

ACOUSTIC PULSE-ECHO RANGING SYSTEMS

the specification of which

(Check ☒ [X] is attached hereto.
one)

[] was filed on _____
Application Serial No. _____
and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 (a)-(d) of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

Priority
Claimed

9823059.2 United Kingdom 21 October 1998
(Number) (Country) (Day/Month/Year Filed)

[x] []
Yes No

(Number) (Country) (Day/Month/Year Filed)

[] []
Yes No

(Number) (Country) (Day/Month/Year Filed)

[] []
Yes No

I hereby claim the benefit under Title 35, United States Code, §119(e) of any United States provisional application(s) listed below.

(Application Serial No.)

(Filing Date)

(Application Serial No.)

(Filing Date)

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application (s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)

(Filing Date)

(Status)
(Patented, pending,
abandoned)

(Application Serial No.)

(Filing Date)

(Status)
(Patented, pending,
abandoned)

POWER OF ATTORNEY

I hereby appoint P.E. McArdle (Registration No. 26,138), R.A.R. Parsons (Registration No. 28,159), P.K. Holland (Registration No. 28,174), J.R. Lake (Registration No. 31,081), R.S. Mitchell (Registration No. 31,228), Robert G. Hirons (Registration No. 24,666), and W.B. Vass (Registration No. 36,416), telephone No. (416) 868-1482 as my attorneys or agents to prosecute this application, to make alterations and amendments therein, to receive the patent and all correspondence relating to this application, and to transact all business in the U.S. Patent and Trademark Office connected therewith, and the said attorneys or agents are hereby given full power of substitution and revocation.

Address all correspondence and telephone calls to:

Richard A.R. Parsons,
c/o Ridout & Maybee,
Suite 2400,
One Queen Street East,
Toronto, Ontario M5C 3B1,
C A N A D A.

Telephone No.: (416) 868-1482

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Quinton Lyon

Full name of sole or first
inventor

Full name of second joint
inventor, if any

Inventor's Signature

Inventor's Signature

Date South African
Citizenship

Date _____
Citizenship

2294 Woodglade Boulevard
Residence

Residence

Peterborough, Ontario
Canada K9K 1T9

As above

Post Office Address

Post Office Address